		Page : 1
	SAFETY DATA SHEET	Revised edition no : 2
• Air Liquide		Revision date : 10 / 7 / 2018
		Supersedes : 23 / 2 / 2016
	ALIGAL 16	1071004
	2.2 : Non flammable, non toxic gas.	
Warning		
SECTION 1. Identification of	the substance/mixture and of the company/underta	king
Product identifier		
Trade name	: ALIGAL 16	
SDS Nr	: 1071004	
	he substance or mixture and uses advised against	
Relevant identified uses	<ul> <li>East and have an analyzed and have been and and anti-</li> </ul>	
Nelevant identified uses		onal. Perform risk assessment prior to
	use. Contact supplier for more application information.	
Details of the supplier of the Company identification	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA	
Details of the supplier of the	use. Contact supplier for more application information. <b>e safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100	
Details of the supplier of the Company identification	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com	
Details of the supplier of the Company identification E-Mail address (competent	use. Contact supplier for more application information. <b>e safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com per per : +27 87 288 1100	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifie	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel. : +27 87 288 1100 person) : scr.sales@airliquide.com Per ber : +27 87 288 1100 cation	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com her ber : +27 87 288 1100 cation	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar Hazard Class and Category Co	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com Per ber : +27 87 288 1100 cation <u>nce or mixture</u> bde Regulation EC 1272/2008 (CLP)	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel. : +27 87 288 1100 person) : scr.sales@airliquide.com <u>her</u> ber : +27 87 288 1100 cation <u>nce or mixture</u> bde Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifie Classification of the substar Hazard Class and Category Co • Physical hazards	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel. : +27 87 288 1100 person) : scr.sales@airliquide.com <u>her</u> ber : +27 87 288 1100 cation <u>nce or mixture</u> bde Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifie Classification of the substar Hazard Class and Category Co • Physical hazards	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com <b>her</b> ber : +27 87 288 1100 <b>cation</b> <b>hce or mixture</b> bde Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL C 1999/45	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com her ber : +27 87 288 1100 cation <u>hce or mixture</u> bede Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL C 1999/45 : Not classified as dangerous substance/mixture.	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifient Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC Label elements	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com her ber : +27 87 288 1100 cation <u>hce or mixture</u> bede Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL C 1999/45 : Not classified as dangerous substance/mixture.	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC Label elements Labelling Regulation EC 1272/2	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com her ber : +27 87 288 1100 cation <u>hce or mixture</u> bede Regulation EC 1272/2008 (CLP) : Gases under pressure - Liquefied gas - Warning - (CL C 1999/45 : Not classified as dangerous substance/mixture.	
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifie Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC Label elements Labelling Regulation EC 1272/ • Hazard pictograms	use. Contact supplier for more application information. <b>a safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel. : +27 87 288 1100 person) : scr.sales@airliquide.com <b>ner</b> <b>ber</b> : +27 87 288 1100 <b>cation</b> <b>cation</b> <b>i</b> Gases under pressure - Liquefied gas - Warning - (CL <b>2 1999/45</b> : Not classified as dangerous substance/mixture. <b>2008 (CLP)</b> <b>i</b> GHS04 : Warning	P : Press. Gas) - H280
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC Label elements Labelling Regulation EC 1272/7 • Hazard pictograms • Hazard pictograms code • Signal word • Hazard statements	use. Contact supplier for more application information. <b>2 safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com <b>Per</b> <b>ber</b> : +27 87 288 1100 <b>cation</b> <b>10ce or mixture</b> <b>bde Regulation EC 1272/2008 (CLP)</b> : Gases under pressure - Liquefied gas - Warning - (CL <b>C 1999/45</b> : Not classified as dangerous substance/mixture. <b>2008 (CLP)</b> <b>i</b> GHS04 : Warning : H280 - Contains gas under pressure; may explode if h	P : Press. Gas) - H280
Details of the supplier of the Company identification E-Mail address (competent Emergency telephone numb Emergency telephone numb SECTION 2. Hazards identifi Classification of the substar Hazard Class and Category Co • Physical hazards Classification EC 67/548 or EC Label elements Labelling Regulation EC 1272/ • Hazard pictograms	use. Contact supplier for more application information. <b>2 safety data sheet</b> : AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100 person) : scr.sales@airliquide.com <b>Per</b> <b>ber</b> : +27 87 288 1100 <b>cation</b> <b>10ce or mixture</b> <b>bde Regulation EC 1272/2008 (CLP)</b> : Gases under pressure - Liquefied gas - Warning - (CL <b>C 1999/45</b> : Not classified as dangerous substance/mixture. <b>2008 (CLP)</b> <b>i</b> GHS04 : Warning : H280 - Contains gas under pressure; may explode if h	P : Press. Gas) - H280



Page : 2 Revised edition no : 2

Revised edition no : 2 Revision date : 10 / 7 / 2018

Supersedes : 23 / 2 / 2016

1071004

## ALIGAL 16

#### **SECTION 2. Hazards identification (continued)**

#### Other hazards

: Asphyxiant in high concentrations.

#### SECTION 3. Composition/information on ingredients

#### Substance / 3.2. Mixture

Mixture.

Substance name		Contents	CAS No	EC No	Index No	Registration no	Classification
Carbon dioxide	:	60 %	124-38-9	204-696-9		* 1	Not classified (DSD/DPD)  Liq. Gas (H280)
Nitrogen	:	40 %	7727-37-9	231-783-9		*1	Not classified (DSD/DPD)  Press. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

\* 1: Listed in Annex IV / V REACH, exempted from registration.

\* 2: Registration deadline not expired.

\* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

### **SECTION 4.** First aid measures

#### Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact	: For liquid spillage - flush with water for at least 15 minutes.
- Eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion	: Ingestion is not considered a potential route of exposure.
Most important symptoms	and effects, both acute and delayed
	: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/

- consciousness. Victim may not be aware of asphyxiation.
  - Refer to section 11.

#### Indication of any immediate medical attention and special treatment needed

: None.

### SECTION 5. Fire-fighting measures

#### Extinguishing media - Suitable extinguishing media : All known extinguishants can be used. Special hazards arising from the substance or mixture Specific hazards : Exposure to fire may cause containers to rupture/explode. Hazardous combustion products : None Advice for fire-fighters Specific methods : Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains. If possible, stop flow of product. Special protective equipment for fire : In confined space use self-contained breathing apparatus. fighters



Page : 3 Revised edition no : 2

Revision date : 10 / 7 / 2018

Supersedes : 23 / 2 / 2016

## ALIGAL 16

1071004

### **SECTION 6.** Accidental release measures

Personal precautions, protective equi	ipment and emergency procedures
	<ul> <li>Evacuate area. Try to stop release. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Monitor concentration of released product.</li> </ul>
Environmental precautions	
	: Try to stop release.
Methods and material for containmen	nt and cleaning up
	: Ventilate area.
Reference to other sections	
	: See also sections 8 and 13.
SECTION 7. Handling and storage	

Precautions for safe handling	
Safe use of the product	<ul> <li>Protect eyes, face and skin from liquid splashes.</li> <li>Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.</li> <li>Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety procedures.</li> <li>Do not smoke while handling product.</li> <li>Ensure the complete gas system was (or is regularily) checked for leaks before use.</li> </ul>
Safe handling of the gas receptacle	<ul> <li>Refer to supplier's container handling instructions.</li> <li>Do not allow backfeed into the container.</li> <li>Protect cylinders from physical damage; do not drag, roll, slide or drop.</li> <li>When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.</li> <li>Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.</li> <li>If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.</li> <li>Never attempt to repair or modify container valves or safety relief devices.</li> <li>Damaged valves should be reported immediately to the supplier.</li> <li>Keep container valve outlets clean and free from contaminates particularly oil and water.</li> <li>Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.</li> <li>Close container valve after each use and when empty, even if still connected to equipment.</li> <li>Never attempt to transfer gases from one cylinder/container to another.</li> <li>Never use direct flame or electrical heating devices to raise the pressure of a container.</li> <li>Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.</li> </ul>
Conditions for safe storage, includi	ng any incompatibilities
	: Keep away from combustible materials. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers

 Steep container below 50°C in a well ventilated place.

 Observe all regulations and local requirements regarding storage of containers.

 Containers should not be stored in conditions likely to encourage corrosion.

 Containers should be stored in the vertical position and properly secured to prevent toppling.

 Stored containers should be periodically checked for general condition and leakage.

 Container valve guards or caps should be in place.

 Store containers in location free from fire risk and away from sources of heat and ignition.

 Store containers in location free from fire risk and away from sources of heat and ignition.

 Store.



Page: 4

Revised edition no : 2

Revision date : 10 / 7 / 2018 Supersedes : 23 / 2 / 2016

## ALIGAL 16

1071004

### SECTION 7. Handling and storage (continued)

### **SECTION 8. Exposure controls/personal protection**

Control parameters	
Occupational Exposure Limits	
Carbon dioxide	: ILV (EU) - 8 H - [mg/m³] : 9000
	: ILV (EU) - 8 H - [ppm] : 5000
	: TLV© -TWA [ppm] : 5000
	: TLV© -STEL [ppm] : 30000
DNEL: Derived no effect level	: None available.
PNEC: Predicted no effect concentration	: None available.
Exposure controls	
Appropriate engineering controls	<ul> <li>Oxygen detectors should be used when asphixiating gases may be released. Provide adequate general and local exhaust ventilation.</li> <li>Ensure exposure is below occupational exposure limits (where available).</li> <li>Systems under pressure shoud be regularily checked for leakages.</li> <li>Consider work permit system e.g. for maintenance activities.</li> </ul>
Individual protection measures, e.g. personal protective equipment	: Wear goggles and a face shield when transfilling or breaking transfer connections A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Wear safety glasses with side shields Wear leather safety gloves and safety shoes when handling cylinders.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## **SECTION 9.** Physical and chemical properties

#### Information on basic physical and chemical properties

	Appearance	
	- Physical state at 20°C / 101.3kPa	: Liquefied gas.
	- Colour	: Colourless.
	Odour	: Odourless.
	Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
	pH value	: Not applicable for gas-mixtures.
	Molar mass [g/mol]	: Not applicable for gases and gas-mixtures.
	Melting point [°C]	: Not applicable for gas-mixtures.
	Boiling point [°C]	: Not applicable for gas-mixtures.
	Flash point [°C]	: Not applicable for gas-mixtures.
	Evaporation rate (ether=1)	: Not applicable for gas-mixtures.
	Flammability range [vol% in air]	: Not applicable for gas-mixtures.
	Vapour pressure [20°C]	: Not applicable.
	Relative density, gas (air=1)	: Heavier than air.
	Solubility in water [mg/l]	: No reliable data available.
	Partition coefficient n-octanol/water	: Not applicable for gas-mixtures.
	Viscosity at 20°C [mPa.s]	: Not applicable.
	Explosive Properties	: Not applicable.
<u>Othe</u>	er information	
	Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or be



Page : 5

Revised edition no : 2 Revision date : 10 / 7 / 2018

Supersedes : 23 / 2 / 2016

## ALIGAL 16

1071004

### SECTION 9. Physical and chemical properties (continued)

SECTION 10. Stability and reactivity	
Reactivity	
<b>•</b> •••••••••••••••••••••••••••••••••••	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	
	: None.
Conditions to avoid	
Incompatible materials	: None.
meompatible materials	: Reacts with water to form corrosive acids.
Hazardous decomposition products	
	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11. Toxicological information	on

## Information on toxicological effects

Acute toxicity	: No known toxicological effects from this product.
Rat inhalation LC50 [ppm/4h]	: No data available.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

#### **SECTION 12. Ecological information**

<b>T</b>		
10	<b>XIC</b>	ITV/
	~10	IL Y
-		

	No data available.
Persistence - degradability	
	No data available.
Bioaccumulative potential	
	No data available.
Mobility in soil	
	No data available.
Results of PBT and vPvB assessment	
	No data available.



Page : 6 Revised edition no : 2

Revised edition no : 2 Revision date : 10 / 7 / 2018

Supersedes : 23 / 2 / 2016

## ALIGAL 16

## 1071004

ECTION 12. Ecological information	(continued)
Other adverse offects	
Other adverse effects	. News
Effect on ozone layer	: None.
Effect on the global warming	: Contains greenhouse gas(es) not covered by 842/2006/EC
SECTION 13. Disposal consideration	s
Waste treatment methods	
	: Ensure that the emission levels from local regulations or operating permits are not exceede
	Do not discharge into any place where its accumulation could be dangerous. Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http: www.eiga.org) for more guidance on suitable disposal methods Contact supplier if guidance is required.
Additional information	
	: None.
SECTION 14. Transport information	
UN number	: 3163
Labelling ADR, IMDG, IATA	
	: 2.2 : Non flammable, non toxic gas.
Land transport (ADR/RID)	
H.I. nr	: 20
UN proper shipping name	: LIQUEFIED GAS, N.O.S. (Carbon dioxide, Nitrogen)
Transport hazard class(es)	: 2
Classification code	: 2 A
Packing Instruction(s)	: P200
Tunnel Restriction	: C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E
Sea transport (IMDG)	
Proper shipping name	: LIQUEFIED GAS, N.O.S. (Carbon dioxide, Nitrogen)
Class	: 2.2
Packing group	: P200
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	
Packing instruction	: P200
<u> Air transport (ICAO-TI / IATA-DGR)</u>	
Proper shipping name (IATA)	: LIQUEFIED GAS, N.O.S. (Carbon dioxide, Nitrogen)
Class	: 2.2
Passenger and Cargo Aircraft	: Allowed.
Packing instruction - Passenger and Cargo Aircraft	: 200
Cargo Aircraft only	: Allowed.
Packing instruction - Cargo Aircraft	: 200



Page : 7 Revised edition no

Revised edition no : 2 Revision date : 10 / 7 / 2018

Supersedes : 23 / 2 / 2016

## ALIGAL 16

1071004

### **SECTION 14.** Transport information (continued)

#### Special precautions for user

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

- Before transporting product containers :
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

## **SECTION 15.** Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	
Seveso directive 96/82/EC National legislation	: Not covered.
	: Ensure all national/local regulations are observed.
hemical Safety Assessment	
	: A CSA does not need to be carried out for this product.
CTION 16. Other information	
Indication of changes	: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010
Training advice	: Receptacle under pressure.
List of full text of H-statements in section 3.	: H280 - Contains gas under pressure; may explode if heated.
Further information	: Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / ( EC) 1999/45 DPD.
Further information	

End of document