

Page : 1

Revised edition no : 1

Revision date : 1 / 3 / 2016

Supersedes: 27 / 11 / 2014

Argon

1061000



# **Warning**



## SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Trade name : Crystal Argon

SDS Nr : 1061000

Chemical description : Argon

CAS No :007440-37-1 EC No :231-147-0 Index No :---

**Registration-No.** : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : Ar

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use. Purging. Laboratory use

Contact supplier for more uses information

### Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE (PTY) LTD

Crn Vereeniging Road & Andre Marais Street

Alrode, Alberton

Gauteng SOUTH AFRICA Tel.: +27 87 288 1100

**Emergency telephone number** 

: scr.sales@airliquide.com

icigency telephone number

Emergency telephone number : +27 87 288 1100

## **SECTION 2. Hazards identification**

## Classification of the substance or mixture

E-Mail address (competent person)

## Hazard Class and Category Code Regulation EC 1272/2008 (CLP)

Physical hazards
 Gases under pressure - Compressed gas - Warning - (CLP: Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

: Not classified as dangerous substance/mixture.

Not included in Annex VI. No EC labelling required.

## Label elements

#### Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



**AIR LIQUIDE (PTY) LTD** 

Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA

Tel.: +27 87 288 1100

In case of emergency: +27 87 288 1100



Page: 2

Revised edition no: 1 Revision date: 1/3/2016

Supersedes: 27 / 11 / 2014

**Argon** 

1061000

#### **SECTION 2. Hazards identification (continued)**

: GHS04 • Hazard pictograms code Signal word : Warning

 Hazard statements : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Storage : P403 - Store in a well-ventilated place.

Other hazards

: Asphyxiant in high concentrations.

### SECTION 3. Composition/information on ingredients

#### Substance / 3.2. Mixture

Substance.

Substance name Contents **CAS No** EC No Index No Registration no Classification 100 % 7440-37-1 231-147-0 Not classified (DSD/DPD) Argon \* 1 Press. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

1: Listed in Annex IV / V REACH, exempted from registration.

\* 2: Registration deadline not expired.

\* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

## SECTION 4. First aid measures

### **Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

- Skin contact : Adverse effects not expected from this product. - Eye contact : Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

## Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/

consciousness. Victim may not be aware of asphyxiation.

#### Indication of any immediate medical attention and special treatment needed

: None

### SECTION 5. Fire-fighting measures

## Extinguishing media

Extinguishing media

- Suitable extinguishing media : All known extinguishants can be used.

#### Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None

**Advice for fire-fighters** 

Specific methods : If possible, stop flow of product.

Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray

In case of emergency: +27 87 288 1100

jet from a protected position. Do not empty contaminated fire water into drains.

Special protective equipment for fire : In confined space use self-contained breathing apparatus.

fighters

**AIR LIQUIDE (PTY) LTD** 

Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA



Page: 3

Revised edition no: 1 Revision date: 1/3/2016

Supersedes: 27 / 11 / 2014

## Argon

1061000

## **SECTION 5. Fire-fighting measures (continued)**

#### **SECTION 6. Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

: Try to stop release.

Evacuate area.

Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe.

Ensure adequate air ventilation.

## **Environmental precautions**

: Try to stop release.

#### Methods and material for containment and cleaning up

: Ventilate area.

#### Reference to other sections

: See also sections 8 and 13.

### SECTION 7. Handling and storage

#### Precautions for safe handling

Safe use of the product

: Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

#### Safe handling of the gas receptacle

Refer to supplier's container handling instructions.

Suck back of water into the container must be prevented.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact

supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminates particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder

contents.

#### Conditions for safe storage, including any incompatibilities

Keep container below 50°C in a well ventilated place.

Observe all regulations and local requirements regarding storage of containers. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

In case of emergency: +27 87 288 1100

Containers should not be stored in conditions likely to encourage corrosion.

**AIR LIQUIDE (PTY) LTD** 

Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA



Page: 4

Revised edition no: 1 Revision date: 1/3/2016

Supersedes: 27 / 11 / 2014

**Argon** 

1061000

### SECTION 7. Handling and storage (continued)

Specific end use(s)

: None.

## SECTION 8. Exposure controls/personal protection

Control parameters

**DNEL: Derived no effect level** : None available. PNEC: Predicted no effect : None available.

concentration

**Exposure controls** 

Appropriate engineering controls : Oxygen detectors should be used when asphixiating gases may be released.

Consider work permit system e.g. for maintenance activities

Systems under pressure shoud be regularily checked for leakages.

Provide adequate general and local exhaust ventilation.

Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the

risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

Wear leather safety gloves and safety shoes when handling cylinders.

Wear safety glasses with side shields

**Environmental exposure controls** : None necessary.

#### **SECTION 9. Physical and chemical properties**

### Information on basic physical and chemical properties

**Appearance** 

- Physical state at 20°C / 101.3kPa : Gas. - Colour : Colourless.

Odour : No odour warning properties.

**Odour threshold** : Odour threshold is subjective and inadequate to warn for overexposure.

Molar mass [g/mol] : 40 Melting point [°C] : -189 Boiling point [°C] : -186 Critical temperature [°C]

Flash point [°C] : Not applicable for gases and gas-mixtures. Evaporation rate (ether=1) : Not applicable for gases and gas-mixtures.

Flammability range [vol% in air] : Non flammable. : Not applicable. Vapour pressure [20°C]

Relative density, gas (air=1) : 1.38

Relative density, liquid (water=1) : Not applicable.

Solubility in water [mg/l]

Partition coefficient n-octanol/water : Not applicable for inorganic gases.

Auto-ignition temperature [°C] : Not applicable.

Other information

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

**AIR LIQUIDE (PTY) LTD** 

In case of emergency: +27 87 288 1100 Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA



Page: 5

Revised edition no: 1 Revision date: 1/3/2016

Supersedes: 27 / 11 / 2014

## Argon

1061000

### SECTION 10. Stability and reactivity

Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

**Chemical stability** 

: Stable under normal conditions.

Possibility of hazardous reactions

: None.

**Conditions to avoid** 

: None under recommended storage and handling conditions (see section 7).

Incompatible materials

: For additional information on compatibility refer to ISO 11114

**Hazardous decomposition products** 

: None

## SECTION 11. Toxicological information

#### Information on toxicological effects

**Acute toxicity** : No known toxicological effects from this product.

Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. : No known effects from this product. Carcinogenicity Germ cell mutagenicity : No known effects from this product. Reproductive toxicity : No known effects from this product. STOT-single exposure : No known effects from this product. : No known effects from this product. STOT-repeated exposure **Aspiration hazard** : Not applicable for gases and gas-mixtures.

## **SECTION 12. Ecological information**

**Toxicity** 

: No known ecological damage caused by this product.

Persistence - degradability

: No data available.

**Bioaccumulative potential** 

: No data available.

Mobility in soil

: No data available.

Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

Other adverse effects

Effect on ozone layer : None. Effect on the global warming : None.

**AIR LIQUIDE (PTY) LTD** 

In case of emergency: +27 87 288 1100 Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA



Page: 6

Revised edition no: 1 Revision date: 1/3/2016

Supersedes: 27 / 11 / 2014

## Argon

1061000

#### SECTION 13. Disposal considerations

## Waste treatment methods

: Do not discharge into any place where its accumulation could be dangerous.

May be vented to atmosphere in a well ventilated place.

## **Additional information**

: None

### SECTION 14. Transport information

**UN** number : 1006

Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

#### Land transport (ADR/RID)

H.I. nr : 20

: ARGON, COMPRESSED UN proper shipping name

Transport hazard class(es) : 2 Classification code : 1 A Packing Instruction(s) : P200

**Tunnel Restriction** : E : Passage forbidden through tunnels of category E.

**Environmental hazards** : None.

## Sea transport (IMDG)

Proper shipping name : ARGON, COMPRESSED

Class : P200 Packing group Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-V **Packing instruction** 

#### Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : ARGON, COMPRESSED

Class : 2.2 Passenger and Cargo Aircraft : Allowed. Packing instruction - Passenger and : 200

Cargo Aircraft

Cargo Aircraft only : Allowed. : 200

Packing instruction - Cargo Aircraft

## Special precautions for user

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.

**AIR LIQUIDE (PTY) LTD** 

In case of emergency: +27 87 288 1100 Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA



Page: 7

Revised edition no : 1

Revision date : 1 / 3 / 2016

Supersedes: 27 / 11 / 2014

Argon

1061000

## **SECTION 15. Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

Restrictions on use : None.
Seveso directive 96/82/EC : Not covered.

National legislation

: Ensure all national/local regulations are observed.

**Chemical Safety Assessment** 

: A CSA does not need to be carried out for this product.

### **SECTION 16. Other information**

Indication of changes

Training advice

List of full text of H-statements in

section 3.

Note

**DISCLAIMER OF LIABILITY** 

: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

: The hazard of asphyxiation is often overlooked and must be stressed during operator training.

: H280 - Contains gas under pressure; may explode if heated.

: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

: Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document

In case of emergency: +27 87 288 1100

**AIR LIQUIDE (PTY) LTD** 

Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA