		Page : 1
	SAFETY DATA SHEET	Revised edition no : 0
• Air Liquide		Revision date : 22 / 4 / 2015
		Supersedes : 0 / 0 / 0
HELIUM MI	X - 10ppm CO; 20.9% O2	1541160 - CO; O2
	2.2 : Non flammable, non toxic gas.	
Warning		
SECTION 1. Identification of th	ne substance/mixture and of the company/under	taking
Product identifier		
Trade name	: HELIUM MIX - 10ppm CO; 20.9% O2	
SDS Nr	: 1541160 - CO; O2	
Relevant identified uses of the	substance or mixture and uses advised against	<u>t</u>
Relevant identified uses	: Industrial and professional. Perform risk assessmen Test gas / Calibration gas. Laboratory use Contact s	
Details of the supplier of the s	afety data sheet	
Company identification	: AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100	
E-Mail address (competent per	rson) : scr.sales@airliquide.com	
Emergency telephone number		
Emergency telephone number	: +27 87 288 1100	
SECTION 2. Hazards identifica	tion	
Classification of the substance	e or mixture	
SECTION 2. Hazards identifica Classification of the substance Hazard Class and Category Code	e or mixture	
Classification of the substance	e or mixture Regulation EC 1272/2008 (CLP) : Gases under pressure - Compressed gas - Warning	- (CLP : Press. Gas) - H280
<u>Classification of the substance</u> <u>Hazard Class and Category Code</u> • Physical hazards	e or mixture Regulation EC 1272/2008 (CLP) : Gases under pressure - Compressed gas - Warning	- (CLP : Press. Gas) - H280
<u>Classification of the substance</u> <u>Hazard Class and Category Code</u> • Physical hazards <u>Classification EC 67/548 or EC 1</u>	e or mixture Regulation EC 1272/2008 (CLP) : Gases under pressure - Compressed gas - Warning 999/45 : Not classified as dangerous substance/mixture.	- (CLP : Press. Gas) - H280

Hazard pictograms code
: GHS04
: Warning
Hazard statements
: H280 - Contains gas under pressure; may explode if heated.
Precautionary statements
- Storage
: P403 - Store in a well-ventilated place.



Page: 2 Revised edition no : 0

Revision date : 22 / 4 / 2015 Supersedes: 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 2. Hazards identification (continued)

Other hazards

: None.

SECTION 3. Composition/information on ingredients

Substance / 3.2. Mixture

Mixture.

Substance name	Contents	CAS No	EC No	Index No	Registration no	Classification
Oxygen	: Between 18.81 and 2	22.99 % 7782-44-7	231-956-9	008-001-00-8	* 1	O; R8 Ox. Gas 1 (H270) Press. Gas (H280)
Helium	: Between 71.1891 and 8	37.0089 % 7440-59-7	231-168-5		* 1	Not classified (DSD/DPD) Press. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

Description of first aid measures

- Inhalation	: Adverse effects not expected from this product.
- Skin contact	: Adverse effects not expected from this product.

: Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed

: No effect on living tissue. Refer to section 11.

Indication of any immediate medical attention and special treatment needed

: None

SECTION 5. Fire-fighting measures

Extinguishing media

- Eye contact

- Suitable extinguishing media : All known extinguishants can be used. Special hazards arising from the substance or mixture Specific hazards : Supports combustion. Exposure to fire may cause containers to rupture/explode. Hazardous combustion products : None. Advice for fire-fighters Specific methods : Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains. If possible, stop flow of product.

Special protective equipment for fire : None. fighters



Page : 3

Revised edition no : 0 Revision date : 22 / 4 / 2015

Supersedes : 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
	: Try to stop release.	
Environmental precautions		
	: None.	
Methods and material for containme	nt and cleaning up	
	: None.	
Reference to other sections		
	: See also sections 8 and 13.	
SECTION 7. Handling and storage		
Precautions for safe handling		
Safe use of the product	 Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety procedures. Do not smoke while handling product. Ensure the complete gas system was (or is regularily) checked for leaks before use. 	
Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminates particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. 	
Conditions for safe storage, includin	g any incompatibilities	
	 Keep away from combustible materials. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. 	
<u>Specific end use(s)</u>	: None.	



Page: 4 Revised edition no: 0

Revision date : 22 / 4 / 2015 Supersedes : 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 8. Exposure controls/personal protection

Control parameters	
Occupational Exposure Limits	
DNEL: Derived no effect level	: None available.
PNEC: Predicted no effect concentration	: None available.
Exposure controls	
Appropriate engineering controls	 Systems under pressure shoud be regularily checked for leakages. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.
Individual protection measures, e.g. personal protective equipment	 A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Wear safety glasses with side shields Wear leather safety gloves and safety shoes when handling cylinders.
Environmental exposure controls	: None necessary.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance)
------------	---

	Appearance	
	- Physical state at 20°C / 101.3kPa	: Gas.
	- Colour	: Colourless.
	Odour	: Odourless.
	Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
	pH value	: Not applicable for gas-mixtures.
	Molar mass [g/mol]	: Not applicable for gases and gas-mixtures.
	Melting point [°C]	: Not applicable for gas-mixtures.
	Boiling point [°C]	: Not applicable for gas-mixtures.
	Flash point [°C]	: Not applicable for gas-mixtures.
	Evaporation rate (ether=1)	: Not applicable for gas-mixtures.
	Flammability range [vol% in air]	: Not applicable for gas-mixtures.
	Vapour pressure [20°C]	: Not applicable.
	Relative density, gas (air=1)	: Lighter or similar to air.
	Solubility in water [mg/l]	: Not known, but considered to have low solubility.
	Partition coefficient n-octanol/water	: Not applicable for gas-mixtures.
	Viscosity at 20°C [mPa.s]	: Not applicable.
	Explosive Properties	: Not applicable.
Othe	r information	

Other data

: None.

SECTION 10. Stability and reactivity

Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	
	: Stable under normal conditions.
Possibility of hazardous reactions	
	: None.



Page : 5

Revised edition no : 0

Revision date : 22 / 4 / 2015 Supersedes : 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 10. Stability and reactivity (continued)

Conditions to avoid	
Incompatible materials	

: None.

: None.

Hazardous decomposition products

: None.

SECTION 11. Toxicological information

Information on toxicological effects

Acute toxicity	: No toxicological effects from this product.
Rat inhalation LC50 [ppm/4h]	: • Carbon monoxide : 1880
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

<u>Toxicity</u>	
	: No ecological damage caused by this product.
Persistence - degradability	
	: No data available.
Bioaccumulative potential	
	: No data available.
Mobility in soil	
	: No data available.
Results of PBT and vPvB assessmen	<u>nt</u>
	: Not classified as PBT or vPvB.
Other adverse effects	
Effect on ozone layer	: None.
Effect on the global warming	: Contains greenhouse gas(es) not covered by 842/2006/EC



Revised edition no : 0

Revision date : 22 / 4 / 2015

Page: 6

Supersedes : 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 13. Disposal considerations

Waste treatment methods

: May be vented to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http:// www.eiga.org) for more guidance on suitable disposal methods Contact supplier if guidance is required.

Additional information

: None.

SECTION 14. Transport information

UN number	: 1956
Labelling ADR, IMDG, IATA	
	2
	• 2.2 · Non flammable, par toxic gas
Land transport (ADR/RID)	: 2.2 : Non flammable, non toxic gas.
H.I. nr	: 20
UN proper shipping name	: COMPRESSED GAS, N.O.S. (Helium, Oxygen)
Transport hazard class(es)	: 2
Classification code	: 1 A
Packing Instruction(s)	: P200
Tunnel Restriction	: E : Passage forbidden through tunnels of category E.
<u>Sea transport (IMDG)</u>	
Proper shipping name	: COMPRESSED GAS, N.O.S. (Helium, Oxygen)
Class	: 2.2
Packing group	: P200
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
Packing instruction	: P200
<u> Air transport (ICAO-TI / IATA-DGR)</u>	
Proper shipping name (IATA)	: COMPRESSED GAS, N.O.S. (Helium, Oxygen)
Class	: 2.2
Passenger and Cargo Aircraft	: Allowed.
	: 200
Cargo Aircraft only	: Allowed.
	: 200
Special precautions for user	
	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers :

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.



Page : 7

Revised edition no : 0 Revision date : 22 / 4 / 2015

Supersedes : 0 / 0 / 0

HELIUM MIX - 10ppm CO; 20.9% O2

1541160 - CO; O2

SECTION 14. Transport information (continued)

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	
Seveso directive 96/82/EC	: Not covered.
National legislation	
	: Ensure all national/local regulations are observed.
Chemical Safety Assessment	
	: A CSA does not need to be carried out for this product.

SECTION 16. Other information

Indication of changes	: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010
Training advice	: Receptacle under pressure.
List of full text of R-phrases in section 3.	: R8 : Contact with combustible material may cause fire.
List of full text of H-statements in	: H270 - May cause or intensify fire; oxidizer.
section 3.	H280 - Contains gas under pressure; may explode if heated.
Further information	: Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD. This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document