		Page : 1		
	SAFETY DATA SHEET	Revised edition no : 1		
Air Liquide		Revision date : 24 / 2 / 2016		
		Supersedes : 31 / 10 / 2013		
	Helium	ALSA061A		
2.2 : Non flammable, non toxic gas.				
Warning SECTION 1 Identification of the substance/mixture and of the company/undertaking				
SECTION 1. Identification of the substance/mixture and of the company/undertaking				
Product identifier	Helium			
Trade name SDS Nr	: Helium : ALSA061A			
Chemical description	: Helium CAS No :007440-59-7 EC No :231-168-5 Index No :			
Registration-No.	: Listed in Annex IV / V REACH, exempted from regist	ration.		
Chemical formula	: He			
Relevant identified uses of the substance or mixture and uses advised against				
Relevant identified uses : Industrial and professional. Perform risk assessment prior to use. Purging. Laboratory use Contact supplier for more application information.				
Details of the supplier of the safety data sheet				
Company identification	: AIR LIQUIDE (PTY) LTD Crn Vereeniging Road & Andre Marais Street Alrode, Alberton Gauteng SOUTH AFRICA Tel.: +27 87 288 1100			
E-Mail address (competent	person) : scr.sales@airliquide.com			
Emergency telephone numb				
Emergency telephone numb	ber : +27 87 288 1100			
SECTION 2. Hazards identifi	cation			
Classification of the substar	nce or mixture			
Hazard Class and Category Co	de Regulation EC 1272/2008 (CLP)			
 Physical hazards 	: Gases under pressure - Compressed gas - Warning	- (CLP : Press. Gas) - H280		
Classification EC 67/548 or EC	 Not classified as dangerous substance/mixture. Not included in Annex VI. No EC labelling required. 			
Label elements				
Labelling Regulation EC 1272/	2008 (CLP)			
Hazard pictograms	\wedge			



Page : 2 Revised edition no : 1

Revision date : 24 / 2 / 2016

Supersedes : 31 / 10 / 2013

ALSA061A

Helium

SECTION 2. Hazards identification (continued)

 Hazard pictograms code Signal word 	: GHS04 : Warning
 Hazard statements 	: H280 - Contains gas under pressure; may explode if heated.
 Precautionary statements 	
- Storage	: P403 - Store in a well-ventilated place.
Other hazards	

: Asphyxiant in high concentrations.

SECTION 3. Composition/information on ingredients

Substance / 3.2. Mixture

Substance.

	Substance name		Contents	CAS No	EC No	Index No	Registration no	Classification
Fless. Gas (fi260)	Helium	:	100 %	7440-59-7	231-168-5		* 1	Not classified (DSD/DPD) Press. Gas (H280)

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.	
- Skin contact	: Adverse effects not expected from this product.	
- Eye contact	: Adverse effects not expected from this product.	
- Ingestion	: Ingestion is not considered a potential route of exposure.	
Most important symptoms and effects, both acute and delayed		
	: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.	
Indication of any immediate medical attention and appeals treatment peeded		

Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5. Fire-fighting measures

Extinguishing media

Extinguishing media		
- Suitable extinguishing media	: All known extinguishants can be used.	
Special hazards arising from the substance or mixture		
Specific hazards	: Exposure to fire may cause containers to rupture/explode.	
Hazardous combustion products	: None.	
Advice for fire-fighters		
Specific methods	 Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains. If possible, stop flow of product. 	
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus.	



Page: 3 Revised edition no : 1

Revision date : 24 / 2 / 2016 Supersedes : 31 / 10 / 2013

ALSA061A

Helium

SECTION 5. Fire-fighting measures (continued)

SECTION 6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures		
	 Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. 	
Environmental precautions		
	: Try to stop release.	
Methods and material for containmen	at and cleaning up	
	: Ventilate area.	
Reference to other sections	: See also sections 8 and 13.	

SECTION 7. Handling and storage

Precautions for safe handling

Safe use of the product	 Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety procedures. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not smoke while handling product. Ensure the complete gas system was (or is regularily) checked for leaks before use. 	
Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminates particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. 	
Conditions for safe storage, including any incompatibilities		
	: Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away	

from sources of heat and ignition. Keep away from combustible materials. Containers should not be stored in conditions likely to encourage corrosion.

Specific end use(s)



Page : 4

Revised edition no : 1 Revision date : 24 / 2 / 2016

Supersedes : 31 / 10 / 2013

ALSA061A

Helium

SECTION 7. Handling and storage (continued)

: None.

SECTION 8. Exposure controls/personal protection

Control parameters	
DNEL: Derived no effect level	: None available.
PNEC: Predicted no effect concentration	: None available.
Exposure controls	
Appropriate engineering controls	 Oxygen detectors should be used when asphixiating gases may be released. Consider work permit system e.g. for maintenance activities. Systems under pressure shoud be regularily checked for leakages. Provide adequate general and local exhaust ventilation.
Individual protection measures, e.g. personal protective equipment	 A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Wear safety glasses with side shields Wear leather safety gloves and safety shoes when handling cylinders.
Environmental exposure controls	: None necessary.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

	Appearance	
	- Physical state at 20°C / 101.3kPa	: Gas.
	- Colour	: Colourless.
	Odour	: No odour warning properties.
	Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
	Molar mass [g/mol]	: 4
	Melting point [°C]	: Not applicable for gas-mixtures.
	Boiling point [°C]	: -269
	Critical temperature [°C]	: -268
	Flash point [°C]	: Not applicable for gases and gas-mixtures.
	Evaporation rate (ether=1)	: Not applicable for gases and gas-mixtures.
	Flammability range [vol% in air]	: Non flammable.
	Vapour pressure [20°C]	: Not applicable.
	Relative density, gas (air=1)	: 0.14
	Relative density, liquid (water=1)	: Not applicable.
	Solubility in water [mg/l]	: 1.5
	Partition coefficient n-octanol/water	: Not applicable for inorganic gases.
	Auto-ignition temperature [°C]	: Not applicable.
Othe	r information	
-		

Other data

: None.



Page : 5

Revised edition no : 1 Revision date : 24 / 2 / 2016

Supersedes : 31 / 10 / 2013

Helium

ALSA061A

SECTION 10. Stability and reactivity

<u>Reactivity</u>	
	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	
	: Stable under normal conditions.
Possibility of hazardous reactions	
	: None.
Conditions to avoid	
	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	
	: None. For additional information on compatibility refer to ISO 11114
Hazardous decomposition products	
<u> </u>	: None.

SECTION 11. Toxicological information

Information on toxicological effects

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

<u>Toxicity</u>	
	: No known ecological damage caused by this product.
Persistence - degradability	
	: No data available.
Bioaccumulative potential	
Mehiliw in soil	: No data available.
<u>Mobility in soil</u>	: No data available.
Results of PBT and vPvB assessmen	
	 : Not classified as PBT or vPvB.
Other adverse effects	
Effect on ozone layer	: None.
Effect on the global warming	: None.



Page: 6

Revised edition no : 1

Revision date : 24 / 2 / 2016 Supersedes : 31 / 10 / 2013

Helium

ALSA061A

Waste treatment methods	
	: May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous.
Additional information	Do not discharge into any place where its accumulation could be dangerous.
Additional information	
	: None.
SECTION 14. Transport information	
UN number	: 1046
Labelling ADR, IMDG, IATA	
	: 2.2 : Non flammable, non toxic gas.
Land transport (ADR/RID)	
H.I. nr	: 20
UN proper shipping name	: HELIUM, COMPRESSED
Transport hazard class(es)	: 2
Classification code	: 1 A
Packing Instruction(s)	: P200
Tunnel Restriction	: E : Passage forbidden through tunnels of category E.
Environmental hazards	: None.
Sea transport (IMDG)	
Proper shipping name	: HELIUM, COMPRESSED
Class	: 2.2
Packing group	: P200
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	
Packing instruction	: P200
<u>Air transport (ICAO-TI / IATA-DGR)</u>	
Proper shipping name (IATA)	: HELIUM, COMPRESSED
Class	: 2.2
Passenger and Cargo Aircraft	: Allowed.
Packing instruction - Passenger and Cargo Aircraft	: 200
Cargo Aircraft only	: Allowed.
Packing instruction - Cargo Aircraft only	: 200
Special precautions for user	
	: Avoid transport on vehicles where the load space is not separated from the driver's
	compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in event of an accident or an emergency. Before transporting product containers :

- Before transporting product containers : - Ensure that containers are firmly secured.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.



Page : 7

Revised edition no : 1

Revision date : 24 / 2 / 2016 Supersedes : 31 / 10 / 2013

Helium

ALSA061A

SECTION 15. Regulatory information

EU legislation	
Restrictions on use	: None.
Seveso directive 96/82/EC	: Not covered.
National legislation	
	: Ensure all national/local regulations are observed.
nemical Safety Assessment	
	: A CSA does not need to be carried out for this product.
CTION 16. Other information	
Indication of changes	: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training
•	: The hazard of asphyxiation is often overlooked and must be stressed during operator trainir : H280 - Contains gas under pressure; may explode if heated.
Training advice List of full text of H-statements in	

End of document