

HYDROGEN MIX - 50% CO

1541073 - CO



2.1 : flammable gas.

Danger**SECTION 1. Identification of the substance/mixture and of the company/undertaking****Product identifier**

Trade name : HYDROGEN MIX - 50% CO
SDS Nr : 1541073 - CO

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
Test gas / Calibration gas. Laboratory use Contact supplier for more uses information

Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE (PTY) LTD
Crn Vereeniging Road & Andre Marais Street
Alrode, Alberton
Gauteng SOUTH AFRICA
Tel. : +27 87 288 1100

E-Mail address (competent person) : scr.sales@airliquide.com

Emergency telephone number

Emergency telephone number : +27 87 288 1100

SECTION 2. Hazards identification**Classification of the substance or mixture****Hazard Class and Category Code Regulation EC 1272/2008 (CLP)**

- Health hazards : Acute toxicity, Inhalation - Category 4 - Warning - (CLP : Acute Tox. 4) - H332
Reproductive toxicity - Unborn Child - Category 1A - Danger - (CLP : Repr. 1A) - H360D
Specific Target Organ Toxicity - Repeated exposure - Category 1 - Danger - (CLP : STOT RE 1) - H372
- Physical hazards : Flammable gases - Category 1 - Danger - (CLP : Flam. Gas 1) - H220
Gases under pressure - Compressed gas - Warning - (CLP : Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

: F+; R12
Repr. Cat. 1; R61
T; R23-R48/23

Label elements**Labelling Regulation EC 1272/2008 (CLP)**

- Hazard pictograms



HYDROGEN MIX - 50% CO
1541073 - CO
SECTION 2. Hazards identification (continued)

- **Hazard pictograms code** : GHS02 - GHS08 - GHS07 - GHS04
- **Signal word** : Danger
- **Hazard statements** : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H360D - May damage the unborn child.
H332 - Harmful if inhaled.
H372 - Causes damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
 - **Prevention** : P260 - Do not breathe gas, vapours.
P210 - Keep away from heat, sparks, open flames or hot surfaces. – No smoking.
P202 - Do not handle until all safety precautions have been read and understood.
 - **Response** : P304+P340+P315 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.
P308+P313 - If exposed or concerned : get medical advice.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 - **Storage** : P403 - Store in a well-ventilated place.
P405 - Store locked up.

Other hazards

: None.

SECTION 3. Composition/information on ingredients
Substance / 3.2. Mixture
Mixture.

| Substance name | Contents | CAS No | EC No | Index No | Registration no | Classification |
|-----------------|-----------------------|-----------|-----------|--------------|------------------|---|
| Hydrogen | : Between 45 and 55 % | 1333-74-0 | 215-605-7 | 001-001-00-9 | * 1 | F+; R12 ----- Flam. Gas 1 (H220) Press. Gas (H280) |
| Carbon monoxide | : Between 45 and 55 % | 630-08-0 | 211-128-3 | 006-001-00-2 | 01-2119480165-39 | F+; R12 Repr. Cat. 1; R61 T; R23-48/23 ----- Flam. Gas 1 (H220) Repr. 1A (H360D) Acute Tox. 3 (H331) STOT RE 1 (H372) Press. Gas (H280) |

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures
Description of first aid measures

- **Inhalation** : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- **Skin contact** : Adverse effects not expected from this product.
- **Eye contact** : Adverse effects not expected from this product.
- **Ingestion** : Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed

 : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.
Refer to section 11.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 4. First aid measures (continued)****Indication of any immediate medical attention and special treatment needed**

: Obtain medical assistance.

SECTION 5. Fire-fighting measures**Extinguishing media****- Suitable extinguishing media** : All known extinguishants can be used.**Special hazards arising from the substance or mixture****Specific hazards** : Exposure to fire may cause containers to rupture/explode.**Hazardous combustion products** : Flammable gases.**Advice for fire-fighters****Specific methods** : Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains. If possible, stop flow of product.**Special protective equipment for fire fighters** : Use self-contained breathing apparatus.**SECTION 6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**: Evacuate area.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Try to stop release.
Monitor concentration of released product.
Ensure adequate air ventilation.
Eliminate ignition sources.
Consider the risk of potentially explosive atmospheres.**Environmental precautions**

: Try to stop release.

Methods and material for containment and cleaning up

: Ventilate area.

Reference to other sections

: See also sections 8 and 13.

SECTION 7. Handling and storage**Precautions for safe handling****Safe use of the product** : Avoid exposure, obtain special instructions before use.
Take precautionary measures against static discharge.
Purge air from system before introducing gas.
Keep away from ignition sources (including static discharges).
Do not smoke while handling product.
Assess the risk of potentially explosive atmosphere and the need for explosion-proof equipment.
Consider the use only non-sparking tools.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Only experienced and properly instructed persons should handle gases under pressure.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Ensure the complete gas system was (or is regularly) checked for leaks before use.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 7. Handling and storage (continued)**

- Safe handling of the gas receptacle** :
- Refer to supplier's container handling instructions.
 - Do not allow backfeed into the container.
 - Protect cylinders from physical damage; do not drag, roll, slide or drop.
 - When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
 - Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
 - If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
 - Never attempt to repair or modify container valves or safety relief devices.
 - Damaged valves should be reported immediately to the supplier.
 - Keep container valve outlets clean and free from contaminants particularly oil and water.
 - Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
 - Close container valve after each use and when empty, even if still connected to equipment.
 - Never attempt to transfer gases from one cylinder/container to another.
 - Never use direct flame or electrical heating devices to raise the pressure of a container.
 - Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Conditions for safe storage, including any incompatibilities

- :
- Segregate from oxidant gases and other oxidants in store.
 - All electrical equipment in the storage areas should be compatible with the risk of potentially explosive atmosphere.
 - Keep away from combustible materials.
 - Keep container below 50°C in a well ventilated place.
 - Observe all regulations and local requirements regarding storage of containers.
 - Containers should not be stored in conditions likely to encourage corrosion.
 - Containers should be stored in the vertical position and properly secured to prevent toppling.
 - Stored containers should be periodically checked for general condition and leakage.
 - Container valve guards or caps should be in place.
 - Store containers in location free from fire risk and away from sources of heat and ignition.

Specific end use(s)

- : None.

SECTION 8. Exposure controls/personal protection**Control parameters****Occupational Exposure Limits****Carbon monoxide**

- : TLV[©] -TWA [ppm] : 25
: ILV (EU) - 8 H - [ppm] : 20
: ILV (EU) - 15 min - [mg/m³] : 117
: ILV (EU) - 15 min - [ppm] : 100
: ILV (EU) - 8 H - [mg/m³] : 23

DNEL: Derived no effect level

- : None available.

PNEC: Predicted no effect concentration

- : None available.

Exposure controls**Appropriate engineering controls**

- : Alarm detectors should be used when toxic gases may be released.
Ensure exposure is below occupational exposure limits (where available).
Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Keep concentrations well below lower explosion limits.
Product to be handled in a closed system and under strictly controlled conditions.
Preferably use only permanent leak-tight installations (e.g. welded pipes).
Consider work permit system e.g. for maintenance activities.

Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered.
Wear leather safety gloves and safety shoes when handling cylinders.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 8. Exposure controls/personal protection (continued)**

- Wear safety glasses with side shields
Keep self contained breathing apparatus readily available for emergency use.
Consider the use of flame resistant anti-static safety clothing.
- Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9. Physical and chemical properties**Information on basic physical and chemical properties**

- Appearance**
- Physical state at 20°C / 101.3kPa : Gas.
 - Colour : Colourless.
 - Odour : Odourless.
 - Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.
 - pH value : Not applicable for gas-mixtures.
 - Molar mass [g/mol] : Not applicable for gases and gas-mixtures.
 - Melting point [°C] : Not applicable for gas-mixtures.
 - Boiling point [°C] : Not applicable for gas-mixtures.
 - Flash point [°C] : Not applicable for gas-mixtures.
 - Evaporation rate (ether=1) : Not applicable for gas-mixtures.
 - Flammability range [vol% in air] : Not applicable for gas-mixtures.
 - Vapour pressure [20°C] : Not applicable.
 - Relative density, gas (air=1) : Lighter or similar to air.
 - Solubility in water [mg/l] : No reliable data available.
 - Partition coefficient n-octanol/water : Not applicable for gas-mixtures.
 - Viscosity at 20°C [mPa.s] : Not applicable.
 - Explosive Properties : Not applicable.

Other information

- Other data : None.

SECTION 10. Stability and reactivity**Reactivity**

- : No reactivity hazard other than the effects described in sub-sections below.

Chemical stability

- : Stable under normal conditions.

Possibility of hazardous reactions

- : May react violently with oxidants.
Can form explosive mixture with air.

Conditions to avoid

- : Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Incompatible materials

- : May react violently with combustible materials.

Hazardous decomposition products

- : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 11. Toxicological information****Information on toxicological effects**

| | |
|--|--|
| Acute toxicity | : Harmful if inhaled. |
| Rat inhalation LC50 [ppm/4h] | : • Carbon monoxide : 1880 |
| Skin corrosion/irritation | : No known effects from this product. |
| Serious eye damage/irritation | : No known effects from this product. |
| Respiratory or skin sensitisation | : No known effects from this product. |
| Carcinogenicity | : No known effects from this product. |
| Germ cell mutagenicity | : No known effects from this product. |
| Toxic for reproduction : Fertility | : No known effects from this product. |
| Toxic for reproduction : unborn child | : May cause harm to the unborn child. |
| STOT-single exposure | : No known effects from this product. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not applicable for gases and gas-mixtures. |

SECTION 12. Ecological information**Toxicity**

: No data available.

Persistence - degradability

: No data available.

Bioaccumulative potential

: No data available.

Mobility in soil

: No data available.

Results of PBT and vPvB assessment

: No data available.

Other adverse effects

| | |
|-------------------------------------|--|
| Effect on ozone layer | : None. |
| Effect on the global warming | : Contains greenhouse gas(es) not covered by 842/2006/EC |

SECTION 13. Disposal considerations**Waste treatment methods**

: Avoid discharge to atmosphere.
Do not discharge into any place where its accumulation could be dangerous.
Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods
Do not discharge into areas where there is a risk of forming an explosive mixture with air.
Waste gas should be flared through a suitable burner with flash back arrestor.
Contact supplier if guidance is required.

Additional information

: None.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 14. Transport information**

UN number : 1954

Labelling ADR, IMDG, IATA



: 2.1 : flammable gas.

Land transport (ADR/RID)

H.I. nr : 23

UN proper shipping name : COMPRESSED GAS, FLAMMABLE, N.O.S. (Hydrogen, Carbon monoxide)

Transport hazard class(es) : 2

Classification code : 1 F

Packing Instruction(s) : P200

Tunnel Restriction : B/D Tank carriage: Passage forbidden through tunnels of category B, C, D

Sea transport (IMDG)

Proper shipping name : COMPRESSED GAS, FLAMMABLE, N.O.S. (Hydrogen, Carbon monoxide)

Class : 2.1

Packing group : P200

Emergency Schedule (EmS) - Fire : F-D

Emergency Schedule (EmS) - Spillage : S-U

Packing instruction : P200

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S. (Hydrogen, Carbon monoxide)

Class : 2.1

Passenger and Cargo Aircraft : DO NOT LOAD IN PASSENGER AIRCRAFT.

Cargo Aircraft only : Allowed.

Packing instruction - Cargo Aircraft only : 200

Special precautions for user

- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers :
- Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure cylinder valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

SECTION 15. Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**

Restrictions on use : Restricted to professional users (Annex XVII REACH).

Seveso directive 96/82/EC : Covered

National legislation

: Ensure all national/local regulations are observed.

Chemical Safety Assessment

: A CSA does not need to be carried out for this product.

HYDROGEN MIX - 50% CO**1541073 - CO****SECTION 15. Regulatory information (continued)****SECTION 16. Other information**

- Indication of changes** : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
- Training advice** : Users of breathing apparatus must be trained.
Ensure operators understand the flammability hazard.
Receptacle under pressure.
- List of full text of R-phrases in section 3.** : R12 : Extremely flammable.
R23 : Toxic by inhalation.
R48/23 : Toxic : danger of serious damage to health by prolonged exposure through inhalation.
R61 : May cause harm to the unborn child.
- List of full text of H-statements in section 3.** : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H331 - Toxic if inhaled.
H360D - May damage the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure.
- Further information** : Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.
This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
- DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document